

[Home](#)[Case Studies](#)[Find Distributor](#)[News](#)[Events](#)[Info Request](#)[Backgauges](#)[Controls](#)
[Hurco](#) > [Hurco USA](#) > [Products](#) > [Autobend](#) > [Backgauges](#) > [Autobend S8](#)

## Rigid automatic press brake rear gauge

### Autobend S8 Backgauge

Rigid automatic press brake rear gauges offering speed, accuracy, and repeatability. Heavy duty cross-ribbed cast aluminum frame - durable and strong.



### Autobend S8 Features/Options:

- Adaptable to press brakes ranging from 3' to 16' or more
- Complete hardware installation instructions
- Easy horizontal and vertical adjustments
- Gauge speed up to 800 ipm
- Gauge travel up to 24"
- Single -or- dual drive available
- Gauge holding force up to 400 lbs
- Heavy duty Y-shaped gauge bar
- 1-1/4" diameter guide rods, continuously supported in machined v-grooves

### Specifications

### Autobend S8

Gauge bar length	Up to 14' (4.27 m)
Gauge travel	24" (610 mm)
Vertical adjustment	10" (254 mm)
Horizontal adjustment	9" (229 mm)
Gauge speed	800 ipm (20.32 m/min)
Position accuracy	+/- 0.003" (+/- 0.08 mm)
Gauge repeatability	+/- 0.002" (+/- 0.05 mm)
Gauge holding force	400 lbs (182 kg)
Casting weight	400 lbs (182 kg)
Guide rod diameter	1 1/4" (32 mm)
Gauge uprights diameter	2" (50 mm)
Distance between uprights	N/A
Power requirements	115/230 VAC +/- 10%, 50/60 Hz
Height	6 1/8" (156 mm)
Width	25 3/4" (644 mm)
Depth	39 1/2" (1003 mm)